

ILS 1K

We can, we do and we do it smarter



A New Standard of Innovation and Quality

The **ILS 1K** is a display of pure craftsmanship and ingenuity, with a strong load capacity of 1000kg packed in a nice, clean Scandinavian design. What really separates our product from the competitors is the self-designed construction, which allows for low installation costs, highest possible flexibility and much more.

- 55 different platform sizes to choose from and a shaft pit of only 110mm means we can always offer you a lift that fits exactly to your building.
- Every ILS 1K comes with a full height platform back in a modern design, which also provides you with correct lighting during your ride.
- A fantastic design and construction for an easy and quick installation of only 2-4 days! Plug n' play all the way through.
- Competitive material prices together with the low installation costs make the ILS 1K to one of the *best priced lifts* on the market.

Thanks to our great design, our strong construction and our flexibility, **ILS 1K** fits into all environments, both public and industrial. Hospitals, care homes, arenas, schools, offices, workshops, furniture stores etc. Everywhere where high quality, design, space and lifting capacity are crucial aspects.

Fantastic loading opportunities are provided in every situation by the wide doors that come fully glazed as standard. As an alternative you can of course have the fire rated EI60 doors. All our push buttons are with both tactile and braille text.

Other possible options include: phones, different choices of flooring, locking, voice announcement, automatic door openers, level indicators, arrival bell, glazed shaft panels, lift painted in other RAL colors, elbow buttons, a mirror and more. See next page for examples.

A lift from **Innovation Lift Scandinavia AB** is an investment for an easier and more comfortable everyday life, for a new standard of innovation and quality.

We can, we do and we do it smarter!



Customization of Every Detail

At **ILS** we are proud of our ability to adapt our products to the preferences and wishes of our customers. Every lift that we make can be customized with large range of options for your to choose from. Here is a small selection of the possibilities that we offer:



Hand rail in stainless steel



Level indicator



Key control



Automatic door opener

Telephone



Folding seat

Specifications

Recommended installation	Indoors
Rated load	1000 kg
Rated Speed	max 0,15 m/sec
	max travel height 13m
Height limits	top Height 2,3 mm
Pit depth	110 mm
Stops	5 stops
Standard platform sizes (w x d)	1400 x 2000 / 1400 x 2500 / 1100 x 2200
Standard lift dimensions (w x d)	1830 x 2080 / 1830 x 2580 / 1530 x 2280 *, **
Cut-out size	+ 30 mm on above
Other platform dimensions width	1000 - 1400
Lift dimension (w)	+ 430 mm (+460 mm if door on B-side)
Other platform dimensions depth	1500 - 2500
Lift dimension (d)	+ 80 mm (if door on A & C +110mm)
Cut-out size	+ 30mm
Standard Shaft finish	Laminated sandwich panels in RAL 9003 (white) (T=25mm, H=565mm), Glazed panels optional.
Standard platform finish	RAL 9003 (white) All powder coated, other RAL colours available upon
	request, black rubber flooring.
Doors	Swing doors, doors can be on 3 sides
Drive system	Screw and nut
Control system	PLC
Power supply	380-400V 3-phase 50/60 Hz 16A, frequency converter
Motor	4 kW
Battery emergency lowering	incl. as standard
Door buttons	one touch
Platform buttons	Hold to run
	All buttons with tactile and braille
Certification	MD 2006 / 42 / EC
Manufactured in	Sweden

* If door on side A & C=+30mm

** If door on side B, w=+30mm